

# HNC SERIES

## COUNTERTOP REFRIGERATED DISPLAY CASE

Item # \_\_\_\_\_

Project: \_\_\_\_\_

Qty: \_\_\_\_\_

\*AutoCad available on KCL

HNC SERIES

1/06

Item # 13027

**HNC-90AA-R(L) DIMENSIONS**  
W x D x H

35.4 x 13.6 x 11

**HNC-120AA-R(L) DIMENSIONS**  
W x D x H

47.2 x 13.6 x 11

**HNC-150AA-R(L) DIMENSIONS**  
W x D x H

59.1 x 13.6 x 11

**HNC-180AA-R(L) DIMENSIONS**  
W x D x H

70.9 x 13.6 x 11

**HNC-210AA-R(L) DIMENSIONS**  
W x D x H

82.7 x 13.6 x 11



**HNC-150AA-R**

Shown

- Top glass angles down
- Ceiling easier to clean
- NSF approved thermometer
- Large diameter 1 inch drains at front
- Larger front to back interior, 11 inches
- Interior floor has a radius at all four sides
- Self-contained refrigeration unit - easy to install
- Condenser airflow is in the back and out the side
- Large diameter upper evaporator with tin plating
- Larger condenser face area improves cooling performance
- Slightly taller doors with plastic seal at end, opposite of the handle
- Solid food plates with radius groove to fit sushi foods
- Food plates can be turned upside down and used to improve cooling performance
- R-134A refrigerant

**Model Name**

**HNC - 120AA - R/L**



**Warranty**

Warranty valid in United States, Canada, Puerto Rico, & U.S. Territories. Contact factory for warranty in other countries.

**One Year** - Parts & Labor on entire unit.

**Two Year** - Parts & Labor on compressor, evaporator, air-cooled condenser.

**Five Year** - Parts on: Compressor; Air-cooled condenser.



# H

# oshizaki


## HNC SERIES COUNTERTOP REFRIGERATED DISPLAY CASE

- HNC-90AA**
- HNC-120AA**
- HNC-150AA**
- HNC-180AA**
- HNC-210AA**


- Right or left handed
- Right or left handed
- Right or left handed
- Right or left handed
- Right or left handed

### REFRIGERATED DISPLAY CASE


Model	HNC-90	HNC-120	HNC-150	HNC-180	HNC-210
AC Supply Voltage	1 Phase 115V 60Hz				
Power Supply Capacity	0.47KVA (4.7A)				
Rated Amperage	3.0A				
Starting Amperage	13A				
Electric Consumption	195W				
Saturation Temperature	Approximately 39°F (Ambient Temp. 80°F, No Load)				
Net Capacity	0.95ft <sup>3</sup>	1.48ft <sup>3</sup>	2.01ft <sup>3</sup>	2.54ft <sup>3</sup>	3.07ft <sup>3</sup>
Ambient Temperature	50 - 80° F				
Voltage Variation	Rated Voltage ± 10%				
Exterior Dimensions (W)(D)(H)	35.4" 13.6" 11"	47.2"	59.1"	70.9"	82.7"
Interior Dimensions (W)(D)(H)	21.5" 11.3" 6.2"	33.3"	45.1"	56.9"	68.7"
Exterior	Glass, ABS Plastic, PVC Plastic, Galvanized Steel				
Interior	Glass, ABS Plastic, Stainless Steel				
Insulation	Polyurethane Foam				
Refrigeration System	Convection Cooling				
Sliding Door	2 Pieces		4 Pieces		
Shipping Weight (Lbs.)	65	90	105	120	135
Shipping Dimensions (W)(D)(H)	39.4" 16.9" 18.6"	51.2"	63"	74.8"	86.6"
Accessories	2 Pieces	3 Pieces	4 Pieces	5 Pieces	6 Pieces
Food Mount	2 Pieces	4 Pieces	4 Pieces	4 Pieces	4 Pieces
Plug	1 Piece	1 Piece	1 Piece	1 Piece	1 Piece
Vinyl Hose	1 Piece	2 Pieces	2 Pieces	2 Pieces	2 Pieces
Joint					




**HNC-90AA-R(L)**  
W x D x H  
35.4" x 13.6" x 11"




**HNC-120AA-R(L)**  
W x D x H  
47.2" x 13.6" x 11"



**HNC-150AA-R(L)**  
W x D x H  
59.1" x 13.6" x 11"



**HNC-180AA-R(L)**  
W x D x H  
70.9" x 13.6" x 11"



**HNC-210AA-L(R)**  
W x D x H  
82.7" x 13.6" x 11"

\*Refrigerated Display Case - Not for overnight storage

### ELECTRICAL/HNC SERIES

- 115/60/1

### OPERATING LIMITS

- Ambient Temp Range 50 - 80°F
- Voltage Range 104 - 126V
- Saturation Temp 39°F

### SERVICE

- Removable/cleanable air filters

© HOSHIZAKI AMERICA, INC.

618 Hwy. 74 S., Peachtree City, GA 30269

TEL 1-800-438-6087

FAX 1-800-345-1325

www.hoshizaki.com

Printed in U.S.A.

