



Glass Door Merchandisers

Dual Temperature

Model	Swing Doors	Cu. Ft. Ref - Frzr		# of Shelves	HP Ref - Frzr	Amps (at 115v)	Crated Weight	Cabinet Dimensions L D† H		
GDM-49DT ‡	2	23	23	8	1 ¹ / ₃ 3 ³ / ₄	14.2	645	54	29 ¹ / ₂	78 ¹ / ₄

All dimensions rounded up to the nearest 1/8".

Black and rosewood vinyl exterior available at no extra charge.
 † Depth does not include 1³/₈" for door handle.
 ‡ Requires 115/208-230/60 Hz, single phase, 3 pole, 4 wire circuit.



GDM-49DT

FEATURES/BENEFITS

- Oversized **environmentally friendly refrigeration systems**, factory sealed and prelubricated for long life.
- Dual temperature for zoned refrigeration equipped with **two, self-contained, independent refrigeration systems**.
- Left side refrigerator (134A) maintains **33°F to 38°F temperatures**.
- Right side freezer (R404A) maintains **-10°F temperatures**.
- Exterior, durable and permanent **non-peel or chip white laminated vinyl** (stainless steel available - extra charge).
- Interior - attractive, **NSF approved**, white aluminum with **300 series stainless steel floor**.
- 4" CFC free insulated partition between cabinet sections ensures temperature integrity of each product zone.
- Safety shielded **fluorescent interior lighting** for longer, brighter, shadow-free illumination.
- **Energy efficient, thermal insulated glass doors**.
- Extruded, aluminum door frames.
- Adjustable, **heavy duty, PVC coated wire shelves**.
- Foamed-in-place polyurethane **high density cell insulation** (CFC Free).
- Illuminated sign panel included.
- Positive seal self-closing doors.
- Self-contained system, no plumbing required.
- Bottom mount heavy duty compressors, easy access to service.
- Optional black interiors available. Upcharge and lead times will apply.
- See our website www.truemfg.com for the latest color & sign offerings. **Freezer Compartment Has...**
- Automatic defrost system time-initiated, temperature-terminated.
- Automatic evaporator fan motor delay during defrost cycle.
- **Standard backguard and floor rack** improve airflow.
- Available with optional legs or 2¹/₂" diameter castors.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.