

Display Cases - Deli



Single Duty Deli Cases

Model	Slide Doors	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions		
							L	D†	H
TSID-48-2	2	16	2	1/3	7.6	425	48 1/2	29 1/4	50 1/4
TSID-48-4	4	16	2	1/3	7.6	430	48 1/2	29 1/4	50 1/4
TSID-72-3	3	24	2	1/2	9.4	595	72 1/2	29 1/4	50 1/4
TSID-72-6	6	24	2	1/2	9.4	590	72 1/2	29 1/4	50 1/4
TSID-96-3	3	32	4	1/2	9.8	775	96 1/2	29 1/4	50 1/4
TSID-96-6	6	32	4	1/2	9.8	765	96 1/2	29 1/4	50 1/4

All dimensions rounded up to the nearest 1/8".

† Depth does not include 5/8" for rear door handle.



TSID-48-4

Oversized gravity coil gently drops cold air to preserve sliced meats & deli products.



TSID-96-3

NSF-7 certified cabinets hold open food products.

FEATURES/BENEFITS

- Oversized, **environmentally friendly (134A) gravity coil refrigeration system**. Gravity coil provides high humidity to preserve sliced meats and deli products. Capillary metering assures constant regulation of refrigerant flow.
- Refrigerator **holds ideal 38°F to 40°F** case temperature for fresher deli products.
- Exterior - durable and permanent **non-peel or chip white laminated vinyl**.
- Interior - attractive, **NSF approved**, white aluminum sides and top, **300 series stainless steel floor** with coved corners.
- Positive seal self-closing door preserves interior humidity.
- Versatile and **durable stainless steel top** provides surface for support equipment such as registers and point-of-purchase novelties.
- Exclusive front and rear interior lighting. Three product illuminating light sources for brilliant product display (TSID-72).
- **Fluorescent lamps are low UV emitting** - red meats are enhanced in faithful color.
- Lamps are safety shielded - assures longer, brighter, shadow-free product illumination. Lighting tubes can be replaced without removing product.
- Foamed-in-place **high density polyurethane insulation** (CFC free).
- Automatic defrost time clock.
- Each deli is designed with **energy efficient, "Low-E", thermal glass, extra large product viewing glass** to maximize your cold product presentations. **13° slanted glass** minimizes reflection from overhead lighting.
- Adjustable, **heavy duty, wire shelves**, 10 mil thick, pure grade PVC coating.
- NSF-7 certified cabinets hold open food products.
- Self-contained system.
- Available with optional legs or 2 1/2" or 4" diameter castors.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.